



BAILEY

NEW



MODEL 20171C (SHOWN)



MODEL 20173A (SHOWN)



WOOD SPECIES: OAK AND MAPLE IN 27 FINISHES. SEE PAGE 221.

OPTIONAL FRONT LEG CASTERS AVAILABLE. ADD \$37 LIST FOR SET OF 2 CASTERS.

MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARM MODELS												
20171A	ALL WOOD			\$541								
20171C	UPHOLSTERED SEAT	.75	9		\$561	\$571	\$585	\$605	\$626	\$649	\$678	\$707
DIMENSIONS: W 22.25 D 23.75 H 38.25 SW 18.5 SD 16.75 SH 19 AH 24.5		CARTONED WEIGHT 30 CUBIC FEET 15										
ARMLESS MODEL												
20173A	ALL WOOD			\$510								
20173C	UPHOLSTERED SEAT	.75	9		\$536	\$545	\$560	\$579	\$600	\$623	\$652	\$681
DIMENSIONS: W 18.5 D 23.25 H 38.25 SW 18.5 SD 16.75 SH 19		CARTONED WEIGHT 27 CUBIC FEET 13										

**SPECIFICATIONS FOR COMMUNITY  
BAILEY COLLECTION  
MODELS: 20171A,C – 20173A,C**

**Wood Species:** Oak & maple

**Details of Construction:** All chair parts are constructed from red oak and maple. All lumber is thoroughly air seasoned before kiln drying to a moisture content of 6%. The lumber is allowed to temper before milling. The front posts are made of 2” lumber. Back posts and top slats are manufactured from 1 ¼” lumber. The arms, side rails, stretchers and horizontal back slats are made from 1” lumber. The front and back rails and vertical back slats are made from 1” lumber. All joints are connected together using mortise and tennon construction and glue at each joint. The frame is further reinforced with corner blocks which are glued and screwed to the seat rails. For added stability and strength, a #12 screw is placed through the center of the blocks and into the adjoining leg. The interior seat consists of a seat rim of solid wood with genuine Ultra-Flex rubber sheeting and securely stapled to the rails.

**Finish:** Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

**Hardware:** Each chair is equipped standard with rubber cushion nickel plated glides.

**Upholstery:** Each upholstered seat consists of Ultra-Flex rubber sheeting and 2” high density polyurethane to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, and Technical Bulletin #117.

<b>Dimensions:</b>	<b><u>20171A, C</u></b>	<b><u>20173A, C</u></b>
	Width: 22 ¼”	Width: 18 ½”
	Depth: 23 ¾”	Depth: 22 ¼”
	Height: 38 ¼”	Height: 38 ½”
	Seat Width: 18 ½”	Seat Width: 18 ½”
	Seat Depth: 16 ¾”	Seat Depth: 16 ¾”
	Seat Height: 19”	Seat Height: 18”
	Arm Height: 24 ½”	