



MODEL 3A (SHOWN)



MODEL 4C (SHOWN)



MODEL 5A (SHOWN)

 ALL BISON MODELS ON GSA CONTRACT.

WOOD SPECIES: OAK AND MAPLE IN 27 FINISHES. SEE PAGE 221.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
BARSTOOL 18"H MODELS												
3A	ALL WOOD			\$162								
3C	UPHOLSTERED SEAT	.75	9		\$208	\$218	\$232	\$252	\$273	\$296	\$325	\$354
DIMENSIONS: W 14.25 D 14.25 H 18 SW 14 SD 14 SH 18 CARTONED WEIGHT 13 CUBIC FEET 4												
BARSTOOL 24"H MODELS												
4A	ALL WOOD			\$171								
4C	UPHOLSTERED SEAT	.75	9		\$216	\$226	\$240	\$259	\$281	\$304	\$333	\$362
DIMENSIONS: W 16.5 D 16.5 H 24 SW 14 SD 14 SH 24 CARTONED WEIGHT 15 CUBIC FEET 6												
BARSTOOL 24"H MODELS												
5A	ALL WOOD			\$192								
5C	UPHOLSTERED SEAT	.75	9		\$238	\$248	\$262	\$281	\$303	\$326	\$355	\$384
DIMENSIONS: W 17.5 D 17.5 H 30 SW 14 SD 14 SH 30 CARTONED WEIGHT 18 CUBIC FEET 7												

**SPECIFICATIONS FOR COMMUNITY
BISON COLLECTION
MODELS: 3A, C – 4A, C – 5A, C**

Wood Species: Oak or Maple

Details of Construction: All chair parts are constructed from solid wood. The front posts are fabricated from 1 ½” lumber. The front and back rails are made from 1” lumber as well as the stretchers. The rail joints are connected together with mortise and tennon and assembly glue at each joint. The stretcher joints are connected together with a solid wood, round tennon and assembly glue at each joint.

Finish: Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Hardware: Each chair is equipped standard with rubber cushion nickel plated glides.

Upholstery: Each seat is upholstered with 4” high density polyurethane to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

Dimensions:	<u>3A, C</u>	<u>4A,C</u>	<u>5A,C</u>
	Width: 14 ¼”	Width: 16 ½”	Width: 17 ½”
	Depth: 14 ¼”	Depth: 16 ½”	Depth: 17 ½”
	Height: 18”	Height: 24”	Height: 30”
	Seat Width: 14”	Seat Width: 14”	Seat Width: 14”
	Seat Depth: 14”	Seat Depth: 14”	Seat Depth: 14”
	Seat Height: 18”	Seat Height: 24”	Seat Height: 30”