

CHANCELLOR



MODEL 331C (SHOWN)



MODEL 333C (SHOWN)



MODEL 338C (SHOWN)


WOOD SPECIES: OAK IN 14 FINISHES. SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED WITH FLEX-WEB FOR ADDED COMFORT AND SUPPORT.

OPTIONAL CASTERS AVAILABLE ON ALL LEGS. ADD \$75 LIST FOR SET OF 4 CASTERS. NOT AVAILABLE ON BARSTOOLS.

OPTIONAL GANGING BRACKET AVAILABLE FOR ARMLESS CHAIR ONLY. SPECIFY AS AN OPTION WHEN ORDERING. ADD \$20 LIST PER GANGING DEVICE.

OPTIONAL SINGLE TOP HORIZONTAL BACK SLAT AVAILABLE. SPECIFY AS AN OPTION WHEN ORDERING. NO UPCHARGE.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARM MODELS												
331A	ALL WOOD			\$507								
331C	UPHOLSTERED SEAT	.75	9		\$516	\$527	\$537	\$552	\$573	\$594	\$618	\$649
DIMENSIONS: W 24 D 23.5 H 44 SW 18.5 SD 19 SH 18 AH 25.75 CARTONED WEIGHT 28 CUBIC FEET 19												
ARMLESS MODELS												
333A	ALL WOOD			\$476								
333C	UPHOLSTERED SEAT	.75	9		\$486	\$497	\$507	\$522	\$542	\$564	\$588	\$619
DIMENSIONS: W 19 D 23.5 H 44 SW 16.5 SD 19 SH 18 CARTONED WEIGHT 27 CUBIC FEET 15												
BARSTOOL MODELS												
338A	ALL WOOD			\$563								
338C	UPHOLSTERED SEAT	.75	9		\$572	\$583	\$593	\$608	\$628	\$649	\$674	\$703
DIMENSIONS: W 18 D 20.25 H 46 SW 15.5 SD 17 SH 30 CARTONED WEIGHT 34 CUBIC FEET 13												

**SPECIFICATIONS FOR COMMUNITY
CHANCELLOR COLLECTION
MODELS: 331A,C – 333A,C – 338A,C**

Wood Species: Oak

Details of Construction: All chair parts are constructed from red oak. All lumber is thoroughly air seasoned before kiln drying to a moisture content of 6%. The lumber is allowed to temper before milling. The front posts and back posts are manufactured from 1 ½” lumber. The arms, side rails, stretchers and three horizontal back slats are made from 1 ¼” lumber. The front and back rails and vertical back slats are made from 1” lumber. All joints are connected together using mortise and tennon construction and glue at each joint. The frame is further reinforced with corner blocks which are glued and screwed to the seat rails. For added stability and strength, a #12 screw is placed through the center of the blocks and into the adjoining leg. The interior seat consists of a seat rim of solid wood with genuine Ultra-Flex rubber sheeting and securely stapled to the rails.

Finish: Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Hardware: Each chair is equipped standard with rubber cushion nickel plated glides.

Upholstery: Each upholstered seat consists of Ultra-Flex rubber sheeting and 2” high density polyurethane to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, and Technical Bulletin #117.

Dimensions:	<u>331A, C</u>	<u>333A, C</u>	<u>338A, C</u>
	Width: 24”	Width: 19”	Width: 18”
	Depth: 23 ½”	Depth: 23 ½”	Depth: 20 ¼”
	Height: 44”	Height: 44”	Height: 46”
	Seat Width: 18 ½”	Seat Width: 16 ½”	Seat Width: 15 ½”
	Seat Depth: 19”	Seat Depth: 19”	Seat Depth: 17”
	Seat Height: 18”	Seat Height: 18”	Seat Height: 30”
	Arm Height: 25 ¾”		